

Warm climate and Medium temperature

Model(s):	CTC EcoAir C112 + CTC EcoLogic		
Air-to-water heat pump:	Yes	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	199 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	9	kW	Seasonal space heating energy efficiency	ηs	195	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	NA	kW	Tj = -7 °C	COPd	NA	-
Tj = +2 °C	Pdh	8,5	kW	Tj = +2 °C	COPd	2,34	-
Tj = +7 °C	Pdh	5,4	kW	Tj = +7 °C	COPd	4,13	-
Tj = +12 °C	Pdh	2,5	kW	Tj = +12 °C	COPd	6,63	-
Tj = bivalent temperature	Pdh	8,5	kW	Tj = bivalent temperature	COPd	2,34	-
Tj = operation limit temperature	Pdh	8,5	kW	Tj = operation limit temperature	COPd	2,34	-
For air-to-water heat pumps: Tj = -15 °C (if TOL < -20 °C)	Pdh	NA	kW	For air-to-water heat pumps: Tj = -15 °C (if TOL < -20 °C)	COPd	NA	-
Bivalent temperature	Tbiv	2	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	Pcych	NA	kW	Cycling interval efficiency	COPcyc	NA	-
Degradation co-efficient	Cdh	0,90	-	Heating water operating limit temperature	WTOL	75	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0,006	kW	Rated heat output (*)	Psup	0,0	kW
Thermostat-off mode	Pto	0,006	kW	Type of energy input	Electric		
Standby mode	PSB	0,006	kW				
Crankcase heater mode	PCK	0,000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	5600	m³/h
Sound power level, indoors/outdoors	LWA	NA / 53	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m³/h
Annual energy consumption	QHE	2290	kWh				

For heat pump combination heater:

Declared load profile	NA	Efficiency class	NA	Water heating energy efficiency	η_{wh}	NA	%
Daily electricity consumption	<i>Q_{elec}</i>	NA	<i>kWh</i>	Daily fuel consumption	<i>Q_{fuel}</i>	NA	<i>kWh</i>
Annual electricity consumption	<i>AEC</i>	NA	<i>kWh</i>	Annual fuel consumption	<i>AFC</i>	NA	<i>GJ</i>

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

CTC AB, Näsavägen 8, SE-341 34 Ljungby Tel +46 372 88000

www.ctc.se

F0144

260115

Model(s):	CTC EcoAir C112 + CTC EcoLogic		
Air-to-water heat pump:	Yes	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	265 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	8	kW	Seasonal space heating energy efficiency	ηs	261	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	NA	kW	Tj = -7 °C	COPd	NA	-
Tj = +2 °C	Pdh	7,5	kW	Tj = +2 °C	COPd	3,55	-
Tj = +7 °C	Pdh	5,0	kW	Tj = +7 °C	COPd	5,93	-
Tj = +12 °C	Pdh	2,3	kW	Tj = +12 °C	COPd	8,01	-
Tj = bivalent temperature	Pdh	7,5	kW	Tj = bivalent temperature	COPd	3,55	-
Tj = operation limit temperature	Pdh	7,5	kW	Tj = operation limit temperature	COPd	3,55	-
For air-to-water heat pumps: Tj = -15 °C (if TOL < -20 °C)	Pdh	NA	kW	For air-to-water heat pumps: Tj = -15 °C (if TOL < -20 °C)	COPd	NA	-
Bivalent temperature	Tbiv	2	°C	For air-to-water heat pumps: Operation limit temperature	TOL	2	°C
Cycling interval capacity for heating	Pcych	NA	kW	Cycling interval efficiency	COPcyc	NA	-
Degradation co-efficient	Cdh	0,90	-	Heating water operating limit temperature	WTOL	75	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	Poff	0,006	kW	Rated heat output (*)	Psup	0,0	kW
Thermostat-off mode	Pto	0,006	kW	Type of energy input	Electric		
Standby mode	Psb	0,006	kW				
Crankcase heater mode	Pck	0,000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	5600	m³/h
Sound power level, indoors/outdoors	LWA	NA / 52	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m³/h
Annual energy consumption	QHE	2065	kWh				

For heat pump combination heater:

Declared load profile	NA	Efficiency class	NA	Water heating energy efficiency	η_{wh}	NA	%
Daily electricity consumption	<i>Q_{elec}</i>	NA	<i>kWh</i>	Daily fuel consumption	<i>Q_{fuel}</i>	NA	<i>kWh</i>
Annual electricity consumption	<i>AEC</i>	NA	<i>kWh</i>	Annual fuel consumption	<i>AFC</i>	NA	<i>GJ</i>

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Model(s):	CTC EcoAir C112 + CTC EcoLogic			
Air-to-water heat pump:	Yes	Energy efficiency class:	A+++	-
Water-to-water heat pump:	No	Controller class:	VI	-
Brine-to-water heat pump:	No	Controller contribution:	4	%
Low-temperature heat pump:	No	Package efficiency:	154	%
Equipped with a supplementary heater:	No	Package efficiency class:	A+++	-
Heat pump combination heater:	No			

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	9	kW	Seasonal space heating energy efficiency	ηs	150	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	7,8	kW	Tj = -7 °C	COPd	2,24	-
Tj = +2 °C	Pdh	4,8	kW	Tj = +2 °C	COPd	3,72	-
Tj = +7 °C	Pdh	3,1	kW	Tj = +7 °C	COPd	5,05	-
Tj = +12 °C	Pdh	2,6	kW	Tj = +12 °C	COPd	7,81	-
Tj = bivalent temperature	Pdh	7,8	kW	Tj = bivalent temperature	COPd	2,24	-
Tj = operation limit temperature	Pdh	7,4	kW	Tj = operation limit temperature	COPd	1,94	-
For air-to-water heat pumps: Tj = -15 °C (if TOL < -20 °C)	Pdh	NA	kW	For air-to-water heat pumps: Tj = -15 °C (if TOL < -20 °C)	COPd	NA	-
Bivalent temperature	Tbiv	-7	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-10	°C
Cycling interval capacity for heating	Pcych	NA	kW	Cycling interval efficiency	COPcyc	NA	-
Degradation co-efficient	Cdh	0,90	-	Heating water operating limit temperature	WTOL	75	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0,006	kW	Rated heat output (*)	Psup	1,6	kW
Thermostat-off mode	Pto	0,006	kW	Type of energy input	Electric		
Standby mode	PSB	0,006	kW				
Crankcase heater mode	PCK	0,000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	5600	m³/h
Sound power level, indoors/outdoors	LWA	NA / 53	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m³/h
Annual energy consumption	QHE	4870	kWh				

For heat pump combination heater:

Declared load profile	NA	Efficiency class	NA	Water heating energy efficiency	η_{wh}	NA	%
Daily electricity consumption	<i>Q_{elec}</i>	NA	<i>kWh</i>	Daily fuel consumption	<i>Q_{fuel}</i>	NA	<i>kWh</i>
Annual electricity consumption	<i>AEC</i>	NA	<i>kWh</i>	Annual fuel consumption	<i>AFC</i>	NA	<i>GJ</i>

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Model(s):	CTC EcoAir C112 + CTC EcoLogic			
Air-to-water heat pump:	Yes	Energy efficiency class:	A+++	-
Water-to-water heat pump:	No	Controller class:	VI	-
Brine-to-water heat pump:	No	Controller contribution:	4	%
Low-temperature heat pump:	No	Package efficiency:	192	%
Equipped with a supplementary heater:	No	Package efficiency class:	A+++	-
Heat pump combination heater:	No			

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	11	<i>kW</i>	Seasonal space heating energy efficiency	η_s	188	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T j			
T j = -7 °C	<i>Pdh</i>	8,7	<i>kW</i>	T j = -7 °C	<i>COPd</i>	2,84	-
T j = +2 °C	<i>Pdh</i>	5,6	<i>kW</i>	T j = +2 °C	<i>COPd</i>	4,48	-
T j = +7 °C	<i>Pdh</i>	3,6	<i>kW</i>	T j = +7 °C	<i>COPd</i>	6,83	-
T j = +12 °C	<i>Pdh</i>	2,6	<i>kW</i>	T j = +12 °C	<i>COPd</i>	9,97	-
T j = bivalent temperature	<i>Pdh</i>	8,7	<i>kW</i>	T j = bivalent temperature	<i>COPd</i>	2,84	-
T j = operation limit temperature	<i>Pdh</i>	8,2	<i>kW</i>	T j = operation limit temperature	<i>COPd</i>	2,60	-
For air-to-water heat pumps: T j = -15 °C (if TOL < -20 °C)	<i>Pdh</i>	NA	<i>kW</i>	For air-to-water heat pumps: T j = -15 °C (if TOL < -20 °C)	<i>COPd</i>	NA	-
Bivalent temperature	<i>T biv</i>	-7	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	-10	°C
Cycling interval capacity for heating	<i>P cych</i>	NA	<i>kW</i>	Cycling interval efficiency	<i>COPcyc</i>	NA	-
Degradation co-efficient	<i>Cdh</i>	0,90	-	Heating water operating limit temperature	<i>WTOL</i>	75	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P OFF</i>	0,006	<i>kW</i>	Rated heat output (*)	<i>Psup</i>	2,3	<i>kW</i>
Thermostat-off mode	<i>P TO</i>	0,006	<i>kW</i>	Type of energy input	Electric		
Standby mode	<i>P SB</i>	0,006	<i>kW</i>				
Crankcase heater mode	<i>P CK</i>	0,000	<i>kW</i>				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	5600	<i>m³/h</i>
Sound power level, indoors/outdoors	<i>L WA</i>	NA / 52	<i>dB</i>	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	<i>m³/h</i>
Annual energy consumption	<i>Q HE</i>	4540	<i>kWh</i>				

For heat pump combination heater:

Declared load profile	NA	Efficiency class	NA	Water heating energy efficiency	η_{wh}	NA	%
Daily electricity consumption	<i>Q_{elec}</i>	NA	<i>kWh</i>	Daily fuel consumption	<i>Q_{fuel}</i>	NA	<i>kWh</i>
Annual electricity consumption	<i>AEC</i>	NA	<i>kWh</i>	Annual fuel consumption	<i>AFC</i>	NA	<i>GJ</i>

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Model(s):	CTC EcoAir C112 + CTC EcoLogic		
Air-to-water heat pump:	Yes	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	138 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	9	kW	Seasonal space heating energy efficiency	ηs	134	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	5,5	kW	Tj = -7 °C	COPd	2,81	-
Tj = +2 °C	Pdh	3,4	kW	Tj = +2 °C	COPd	4,12	-
Tj = +7 °C	Pdh	3,0	kW	Tj = +7 °C	COPd	5,69	-
Tj = +12 °C	Pdh	2,4	kW	Tj = +12 °C	COPd	7,11	-
Tj = bivalent temperature	Pdh	7,4	kW	Tj = bivalent temperature	COPd	2,09	-
Tj = operation limit temperature	Pdh	5,6	kW	Tj = operation limit temperature	COPd	1,58	-
For air-to-water heat pumps: Tj = -15 °C (if TOL < -20 °C)	Pdh	7,4	kW	For air-to-water heat pumps: Tj = -15 °C (if TOL < -20 °C)	COPd	2,09	-
Bivalent temperature	Tbiv	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-22	°C
Cycling interval capacity for heating	Pcych	NA	kW	Cycling interval efficiency	COPcyc	NA	-
Degradation co-efficient	Cdh	0,90	-	Heating water operating limit temperature	WTOL	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0,006	kW	Rated heat output (*)	Psup	3,6	kW
Thermostat-off mode	Pto	0,006	kW	Type of energy input	Electric		
Standby mode	Psb	0,006	kW				
Crankcase heater mode	Pck	0,000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	5600	m³/h
Sound power level, indoors/outdoors	LWA	NA / 53	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m³/h
Annual energy consumption	QHE	6636	kWh				

For heat pump combination heater:

Declared load profile	NA	Efficiency class	NA	Water heating energy efficiency	η_{wh}	NA	%
Daily electricity consumption	<i>Q_{elec}</i>	NA	<i>kWh</i>	Daily fuel consumption	<i>Q_{fuel}</i>	NA	<i>kWh</i>
Annual electricity consumption	<i>AEC</i>	NA	<i>kWh</i>	Annual fuel consumption	<i>AFC</i>	NA	<i>GJ</i>

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Model(s):	CTC EcoAir C112 + CTC EcoLogic		
Air-to-water heat pump:	Yes	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	173 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	10	kW	Seasonal space heating energy efficiency	ηs	169	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7 °C	Pdh	5,9	kW	Tj = -7 °C	COPd	3,65	-
Tj = +2 °C	Pdh	3,5	kW	Tj = +2 °C	COPd	5,05	-
Tj = +7 °C	Pdh	3,1	kW	Tj = +7 °C	COPd	7,39	-
Tj = +12 °C	Pdh	2,4	kW	Tj = +12 °C	COPd	8,53	-
Tj = bivalent temperature	Pdh	7,8	kW	Tj = bivalent temperature	COPd	2,62	-
Tj = operation limit temperature	Pdh	6,3	kW	Tj = operation limit temperature	COPd	2,13	-
For air-to-water heat pumps: Tj = -15 °C (if TOL < -20 °C)	Pdh	7,8	kW	For air-to-water heat pumps: Tj = -15 °C (if TOL < -20 °C)	COPd	2,62	-
Bivalent temperature	Tbiv	-15	°C	For air-to-water heat pumps: Operation limit temperature	TOL	-22	°C
Cycling interval capacity for heating	Pcych	NA	kW	Cycling interval efficiency	COPcyc	NA	-
Degradation co-efficient	Cdh	0,90	-	Heating water operating limit temperature	WTOL	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	POFF	0,006	kW	Rated heat output (*)	Psup	3,4	kW
Thermostat-off mode	Pto	0,006	kW	Type of energy input	Electric		
Standby mode	PSB	0,006	kW				
Crankcase heater mode	PCK	0,000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	5600	m³/h
Sound power level, indoors/outdoors	LWA	NA / 52	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	NA	m³/h
Annual energy consumption	QHE	5574	kWh				

For heat pump combination heater:

Declared load profile	NA	Efficiency class	NA	Water heating energy efficiency	η_{wh}	NA	%
Daily electricity consumption	<i>Q_{elec}</i>	NA	<i>kWh</i>	Daily fuel consumption	<i>Q_{fuel}</i>	NA	<i>kWh</i>
Annual electricity consumption	<i>AEC</i>	NA	<i>kWh</i>	Annual fuel consumption	<i>AFC</i>	NA	<i>GJ</i>

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

CTC AB, Näsavägen 8, SE-341 34 Ljungby Tel +46 372 88000

www.ctc.se

F0144

260115